



## DECLARATION OF COMPLIANCE

Description	Material	Article Number
Laminated bagasse bowls and trays	Bagasse fibre with PBAT/PLA	205656

Duni declares that the article meets the requirements of:

- Article 3, 11(5), 15 and 17 of Regulation (EC) No 1935/2004 (Framework regulation)
- EU Regulation 2023/2006/EC (GMP)
- EU Regulation 10/2011/EC with amendments
- BfR XXXVI (bagasse)
- Order No. 681 of May 25 (2020) from Danish Ministry of Environment and Food on ban of per- and polyfluoroalkyl substances (PFAS) in paper and cardboard food contact materials.

### Overall migration (1)

According to the above-mentioned regulations, the overall migration does not exceed 10 mg/dm<sup>2</sup> or 60 mg/kg.

### Specific migration (2)

Duni's risk assessment of the product shows that the product contains no monomers or additives subject to restrictions under the plastic regulation 10/2011 and its amendments.

### Area of use

Based on the migration tests and Declaration of Compliance, the article can be used for all kinds of foods under the following conditions:

- Long term storage in chilled conditions or room temperature
- Warm keeping at 70°C for up to 2 h or at 100°C for 15 minutes (hotfill<sup>1</sup>)

The bowls are suitable to use in a microwave oven. However, it is the responsibility of the user of the finished packages to ensure that the package is safe to use in the intended conditions (W/min) taking into account all relevant information e.g. the shape and size of the package and packaged food.

---

<sup>1</sup> Definition from COMMISSION REGULATION (EU) 2016/1416: "hot-fill" means the filling of any article with a food with a temperature not exceeding 100 °C at the moment of filling, after which the food cools down to 50 °C or below within 60 minutes, or to 30 °C or below within 150 minutes.

---

#### DUNI GROUP

P.O. Box 237 | SE-201 22 Malmö | Sweden  
Phone +46 40 10 62 00 | Telefax +46 40 39 66 30 | Visitors Ubåtshallen, Östra Varvsgatan 9a  
Org.No. 5565367488 | Reg.Office Malmö | [www.dunigroup.com](http://www.dunigroup.com)

**Test conditions:**

Migration tests on the article's material performed by an independent institute showed that under the following test conditions overall migration (see 1.) and specific migration (see 2.; SML) fall considerably below the respective limits given by regulation 10/2011.

*Overall migration OM5<sup>2</sup>*

<i>Simulant</i>	<i>Contact time</i>	<i>Temperature</i>	<i>Result (mg/dm<sup>3</sup>)</i>
10 % Ethanol	2 hours	100°C	< 3
3% Acetic acid	2 hours	100°C	< 3
95 % Ethanol	4 hours	60°C	< 3
Isooctane	2 hours	60°C	< 3

*Overall migration OM2<sup>3</sup>*

<i>Simulant</i>	<i>Contact time</i>	<i>Temperature</i>	<i>Result (mg/dm<sup>3</sup>)</i>
10 % Ethanol	10 days	40°C	< 3
3% Acetic acid	10 days	40°C	< 3
95 % Ethanol	10 days	40°C	< 3
Isooctane	2 days	20°C	< 3

*Specific migration of PAA*

<i>Simulant</i>	<i>Contact time</i>	<i>Temperature</i>	<i>Result (mg/kg)</i>
3% Acetic acid	2 hours	100°C	< 0,01

The ratio of surface area to volume is 5,4 dm<sup>2</sup>/kg.

No substances of dual use are present in the product.

Please be advised that Duni AB does not add anything into the product.

This document of compliance is based on:

- Documentation from suppliers
- Global migration test

This document was issued electronically and is therefore valid without signature.

---

<sup>2</sup> OM5 test conditions corresponds to intended food contacts conditions "High temperature applications up to 121 °C" according to EU Regulation 10/2011/EC.

<sup>3</sup> OM2 standardised testing conditions corresponds to any long-term storage at room temperature or below, including heating up to 70 °C for up to 2 hours, or heating up to 100 °C for up to 15 minutes as defined in Annex V, Chapter 3, table 3 in COMMISSION REGULATION (EU) No 10/2011 on plastic materials and articles intended to come into contact with food.