

# SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

Detectaplast®

## AlcoSol

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : AlcoSol  
Registration number REACH : Not applicable (mixture)  
Product type REACH : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1 Relevant identified uses

Biocide  
Disinfectant

##### 1.2.2 Uses advised against

No uses advised against known

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier of the safety data sheet

Ortho Medic Care nv  
Evolis 100  
8500 Kortrijk  
☎ +32 56 13 03 35  
☎ +32 56 13 03 39  
sales@detectaplast.be  
www.detectaplast.be

##### Manufacturer of the product

Ortho Medic Care nv  
Evolis 100  
8500 Kortrijk  
☎ +32 56 13 03 35  
☎ +32 56 13 03 39  
sales@detectaplast.be  
www.detectaplast.be

#### 1.4. Emergency telephone number

During business hours :  
+32 55 610 544

24h/24h :

België/Belgique - Antigifcentrum/Centre Antipoisons: +32 70 245 245  
Belgien - Giftinformationszentrum: +32 70 245 245

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Flam. Liq.	category 2	H225: Highly flammable liquid and vapour.
Eye Irrit.	category 2	H319: Causes serious eye irritation.

#### 2.2. Label elements



Signal word

Danger

H-statements

H225

Highly flammable liquid and vapour.

H319

Causes serious eye irritation.

P-statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243

Take action to prevent static discharges.

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370 + P378

In case of fire: Use suitable extinguishing medium to extinguish.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel

<http://www.big.be>

© BIG vzw

Reason for revision: 1.4

Revision number: 0101

Publication date: 2008-12-04

Date of revision: 2021-07-15

BIG number: 61280

1 / 15

878-17926-022-en

# AlcoSol

P403 + P235  
P501

Store in a well-ventilated place. Keep cool.  
Dispose of contents/container in accordance with local/regional/national/international regulation.

## 2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
butanone	78-93-3 201-159-0	1%≤C<10%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	(1)(2)(10)	Constituent	
ethanol 01-2119457610-43	64-17-5 200-578-6	C>25 %	Flam. Liq. 2; H225 Eye Irrit. 2; H319	(1)(2)(6)(10)	Active substance	

(1) For H- and EUH-statements in full: see section 16

(2) Substance with a Community workplace exposure limit

(6) Enumerated in Annex VI of Regulation (EC) No. 1272/2008 but the classification has been adapted after evaluation of available test data

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General:

Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

#### After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

#### After skin contact:

Rinse with water. Do not apply (chemical) neutralizing agents without medical advice. Soap may be used. Take victim to a doctor if irritation persists.

#### After eye contact:

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Do not apply (chemical) neutralizing agents without medical advice. Take victim to an ophthalmologist if irritation persists.

#### After ingestion:

Rinse mouth with water. Do not induce vomiting. Do not apply (chemical) neutralizing agents without medical advice. Consult a doctor/medical service if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

##### After inhalation:

Dizziness. Respiratory difficulties.

##### After skin contact:

ON CONTINUOUS EXPOSURE/CONTACT: Dry skin. Cracking of the skin.

##### After eye contact:

Irritation of the eye tissue.

##### After ingestion:

Vomiting. Abdominal pain. Nausea.

#### 4.2.2 Delayed symptoms

No effects known.

### 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### 5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting class B foam extinguisher, Quick-acting CO2 extinguisher.  
Major fire: Class B foam (alcohol-resistant), Water spray if puddle cannot expand.

#### 5.1.2 Unsuitable extinguishing media:

Reason for revision: 1.4

Publication date: 2008-12-04

Date of revision: 2021-07-15

Revision number: 0101

BIG number: 61280

2 / 15

# AlcoSol

Small fire: Water (quick-acting extinguisher, reel); risk of puddle expansion.

Major fire: Water; risk of puddle expansion.

## 5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO<sub>2</sub> are formed.

## 5.3. Advice for firefighters

### 5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Do not move the load if exposed to heat.

### 5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN 166). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

#### 6.1.1 Protective equipment for non-emergency personnel

See section 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN 166). Protective clothing (EN 14605 or EN 13034).

#### Suitable protective clothing

See section 8.2

### 6.2. Environmental precautions

Contain released product. Dam up the liquid spill. Try to reduce evaporation. Prevent spreading in sewers.

### 6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material, e.g.: sand, saw dust or kieselguhr. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

### 6.4. Reference to other sections

See section 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 7.1. Precautions for safe handling

Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Insufficient ventilation: take precautions against electrostatic charges. Keep away from naked flames/heat. Insufficient ventilation: keep naked flames/sparks away. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards. Do not discharge the waste into the drain. Keep container tightly closed.

### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1 Safe storage requirements:

Store in a dry area. Ventilation at floor level. Fireproof storeroom. Provide for an automatic sprinkler system. Meet the legal requirements.

#### 7.2.2 Keep away from:

Heat sources, ignition sources, oxidizing agents, (strong) acids, metals.

#### 7.2.3 Suitable packaging material:

HDPE.

#### 7.2.4 Non suitable packaging material:

No data available

### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 Occupational exposure

##### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

#### EU

Butanone	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	200 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	600 mg/m <sup>3</sup>
	Short time value (Indicative occupational exposure limit value)	300 ppm
	Short time value (Indicative occupational exposure limit value)	900 mg/m <sup>3</sup>

#### Belgium

Reason for revision: 1.4

Publication date: 2008-12-04

Date of revision: 2021-07-15

Revision number: 0101

BIG number: 61280

3 / 15

# AlcoSol

2-Butanone	Time-weighted average exposure limit 8 h	200 ppm
	Time-weighted average exposure limit 8 h	600 mg/m <sup>3</sup>
	Short time value	300 ppm
	Short time value	900 mg/m <sup>3</sup>
Alcool éthylique	Time-weighted average exposure limit 8 h	1000 ppm
	Time-weighted average exposure limit 8 h	1907 mg/m <sup>3</sup>

## The Netherlands

2-Butanon	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	197 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	590 mg/m <sup>3</sup>
	Short time value (Public occupational exposure limit value)	300 ppm
	Short time value (Public occupational exposure limit value)	900 mg/m <sup>3</sup>
Ethanol	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	136 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	260 mg/m <sup>3</sup>
	Short time value (Public occupational exposure limit value)	992 ppm
	Short time value (Public occupational exposure limit value)	1900 mg/m <sup>3</sup>

## France

Alcool éthylique	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1000 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1900 mg/m <sup>3</sup>
	Short time value (VL: Valeur non réglementaire indicative)	5000 ppm
	Short time value (VL: Valeur non réglementaire indicative)	9500 mg/m <sup>3</sup>
Méthyléthylcétone	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	200 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	600 mg/m <sup>3</sup>
	Short time value (VRC: Valeur réglementaire contraignante)	300 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	900 mg/m <sup>3</sup>

## Germany

Butanon	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	600 mg/m <sup>3</sup>
Ethanol	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	380 mg/m <sup>3</sup>

## UK

Butan-2-one (methyl ethyl ketone)	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	200 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	300 ppm
	Short time value (Workplace exposure limit (EH40/2005))	899 mg/m <sup>3</sup>
Ethanol	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1000 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1920 mg/m <sup>3</sup>

## USA (TLV-ACGIH)

Ethanol	Short time value (TLV - Adopted Value)	1000 ppm
Methyl ethyl ketone	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	200 ppm
	Short time value (TLV - Adopted Value)	300 ppm

## b) National biological limit values

If limit values are applicable and available these will be listed below.

### Germany

2-Butanon (Methylethylketon) (2-Butanon)	Urin: expositionsende, bzw. schichtende	2 mg/l	
--	---	--------	--

### UK

Butan-2-one (butan-2-one)	Urine: post shift	70 µmol/L	
---------------------------	-------------------	-----------	--

### USA (BEI-ACGIH)

Methyl ethyl ketone (Methyl ethyl ketone)	urine: end of shift	2 mg/L	Nonspecific
---	---------------------	--------	-------------

## 8.1.2 Sampling methods

Reason for revision: 1.4

Publication date: 2008-12-04

Date of revision: 2021-07-15

Revision number: 0101

BIG number: 61280

4 / 15

# AlcoSol

Product name	Test	Number
2-Butanone (MEK) (Methyl ethyl ketone)	NIOSH	2500
2-Butanone (Methyl ethyl ketone)	OSHA	84
2-Butanone (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
2-Butanone (Volatile Organic compounds)	NIOSH	2549
2-Butanone	OSHA	1004
2-Butanone	OSHA	13
ACETONE and METHYL ETHYL KETONE in urine	NIOSH	8319
Ethanol (Volatile Organic compounds)	NIOSH	2549
ethanol	NIOSH	8002
Ethyl Alcohol (Ethanol)(Alcohols I)	NIOSH	1400
Ethyl Alcohol	OSHA	100
MEK	NIOSH	8002
Methyl Ethyl Ketone (ketones I)	NIOSH	2555
Methyl Ethyl Ketone	OSHA	16

### 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

### 8.1.4 Threshold values

#### DNEL/DMEL - Workers

##### butanone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	600 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	1161 mg/kg bw/day	

##### ethanol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	950 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	343 mg/kg bw/day	

#### DNEL/DMEL - General population

##### butanone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	106 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	412 mg/kg bw/day	
	Long-term systemic effects oral	31 mg/kg bw/day	

##### ethanol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	114 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	206 mg/kg bw/day	
	Long-term systemic effects oral	87 mg/kg bw/day	

#### PNEC

##### butanone

Compartments	Value	Remark
Fresh water	55.8 mg/l	
Fresh water (intermittent releases)	55.8 mg/l	
Marine water	55.8 mg/l	
STP	709 mg/l	
Fresh water sediment	284.74 mg/kg sediment dw	
Marine water sediment	284.7 mg/kg sediment dw	
Soil	22.5 mg/kg soil dw	
Oral	1000 mg/kg food	

##### ethanol

Compartments	Value	Remark
Fresh water	0.96 mg/l	
Marine water	0.79 mg/l	
Fresh water (intermittent releases)	2.75 mg/l	
STP	580 mg/l	
Fresh water sediment	3.6 mg/kg sediment dw	
Marine water sediment	2.9 mg/kg sediment dw	
Soil	0.63 mg/kg soil dw	
Oral	0.38 g/kg food	

### 8.1.5 Control banding

If applicable and available it will be listed below.

## 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Insufficient ventilation: take precautions against electrostatic charges. Keep away from naked flames/heat. Insufficient ventilation: keep naked flames/sparks away. Measure the concentration in the air regularly. Work under local exhaust/ventilation.

### 8.2.2 Individual protection measures, such as personal protective equipment

Reason for revision: 1.4

Publication date: 2008-12-04

Date of revision: 2021-07-15

Revision number: 0101

BIG number: 61280

5 / 15

# AlcoSol

Observe normal hygiene standards. Do not eat, drink or smoke during work.

**a) Respiratory protection:**

Respiratory protection not required in normal conditions.

**b) Hand protection:**

Hand protection not required in normal conditions.

**c) Eye protection:**

Eye protection not required in normal conditions.

**d) Skin protection:**

Skin protection not required in normal conditions.

**8.2.3 Environmental exposure controls:**

See sections 6.2, 6.3 and 13

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical form	Liquid
Odour	Alcohol odour
Odour threshold	No data available
Colour	Colourless
Translucency	Clear
Particle size	Not applicable (liquid)
Explosion limits	No data available
Flammability	Highly flammable liquid and vapour.
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available
Kinematic viscosity	No data available
Melting point	No data available
Boiling point	No data available
Relative vapour density	No data available
Vapour pressure	No data available
Solubility	Water ; miscible
Relative density	0.889
Absolute density	889 kg/m <sup>3</sup>
Decomposition temperature	No data available
Auto-ignition temperature	No data available
Flash point	22 °C
pH	No data available

### 9.2. Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard. Neutral reaction.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

**Precautionary measures**

Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Insufficient ventilation: take precautions against electrostatic charges. Keep away from naked flames/heat. Insufficient ventilation: keep naked flames/sparks away.

### 10.5. Incompatible materials

Oxidizing agents, (strong) acids, metals.

### 10.6. Hazardous decomposition products

Upon combustion: CO and CO<sub>2</sub> are formed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### 11.1.1 Test results

**Acute toxicity**

AlcoSol

No (test) data on the mixture available

Reason for revision: 1.4

Publication date: 2008-12-04

Date of revision: 2021-07-15

Revision number: 0101

BIG number: 61280

6 / 15

# AlcoSol

Judgement is based on the relevant ingredients

## butanone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 423	2193 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 8100 mg/kg bw/day	24 h	Rabbit (male)	Experimental value	
Inhalation						Data waiving	

## ethanol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	10470 mg/kg bw		Rat (male / female)	Experimental value	
Dermal						Data waiving	
Inhalation (vapours)	LC50	Equivalent to OECD 403	124.7 mg/l air	4 h	Rat (male / female)	Experimental value	

## **Conclusion**

Not classified for acute toxicity

## **Corrosion/irritation**

### AlcoSol

No (test)data on the mixture available

Classification is based on the relevant ingredients

## butanone

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	Equivalent to OECD 405		24; 72 hours	Rabbit	Experimental value	Single exposure
Skin	Not irritating	OECD 404	4 h	4; 24; 48; 72 hours	Rabbit	Read-across	

## ethanol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	OECD 405	14 day(s)	24; 48; 72 hours	Rabbit	Experimental value	Single treatment
Skin	Not irritating	OECD 404	24 h	1; 2; 3; 4; 5; 7 days	Rabbit	Experimental value	Single treatment

## **Conclusion**

Causes serious eye irritation.

Not classified as irritating to the skin

Not classified as irritating to the respiratory system

## **Respiratory or skin sensitisation**

### AlcoSol

No (test)data on the mixture available

Judgement is based on the relevant ingredients

## butanone

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (female)	Experimental value	

## ethanol

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 429			Mouse (male)	Experimental value	
Inhalation (vapours)	Not sensitizing				Rat (male / female)	Experimental value	

## **Conclusion**

Not classified as sensitizing for inhalation

Not classified as sensitizing for skin

## **Specific target organ toxicity**

### AlcoSol

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Reason for revision: 1.4

Publication date: 2008-12-04

Date of revision: 2021-07-15

Revision number: 0101

BIG number: 61280

7 / 15

# AlcoSol

## butanone

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral								Data waiving
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	5041 ppm		No effect	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Inhalation (vapours)			STOT SE cat.3	Central nervous system	Drowsiness, dizziness			Annex VI

## ethanol

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	LOAEL	Equivalent to OECD 408	3160 mg/kg	Liver; kidney	No effect	7 weeks (daily) - 14 weeks (daily)	Rat (male)	Experimental value
Dermal								Data waiving
Inhalation (vapours)	LOAEC	Equivalent to OECD 453	1.3 mg/l air	Pituitary	Histology	12 month(s)	Rat (male / female)	Read-across

## Conclusion

Not classified for subchronic toxicity

## Mutagenicity (in vitro)

### AlcoSol

No (test)data on the mixture available

Judgement is based on the relevant ingredients

### butanone

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Rat liver cells	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	

### ethanol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value	

## Mutagenicity (in vivo)

### AlcoSol

No (test)data on the mixture available

Judgement is based on the relevant ingredients

### butanone

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Intraperitoneal)	Equivalent to OECD 474		Mouse (male / female)		Experimental value

### ethanol

Result	Method	Exposure time	Test substrate	Organ	Value determination
Ambiguous (Oral (stomach tube))	Equivalent to OECD 478	5 days (1x / day)	Mouse (male)	General	Experimental value

## Conclusion

Not classified for mutagenic or genotoxic toxicity

## Carcinogenicity

### AlcoSol

No (test)data on the mixture available

Judgement is based on the relevant ingredients

# AlcoSol

## ethanol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOAEC	Equivalent to OECD 453	≥ 1.3 ppm	24 month(s)	Rat (male / female)	No carcinogenic effect		Read-across
Oral (diet)	NOAEL	Equivalent to OECD 451	> 3000 mg/kg bw/day	104 weeks (daily)	Rat (male / female)	No carcinogenic effect		Experimental value

### Conclusion

Not classified for carcinogenicity

### Reproductive toxicity

#### AlcoSol

No (test) data on the mixture available

Judgement is based on the relevant ingredients

#### butanone

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation)	NOAEC	Equivalent to OECD 414	1002 ppm	10 days (7h / day)	Rat	No effect	Foetus	Experimental value
Maternal toxicity (Inhalation)	NOAEC	Equivalent to OECD 414	1002 ppm	10 days (7h / day)	Rat (female)	No effect		Experimental value
Effects on fertility (Oral (drinking water))	NOAEL	Equivalent to OECD 416	1644 mg/kg bw/day - 1771 mg/kg bw/day		Rat (male / female)	No effect		Experimental value

## ethanol

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEL	Equivalent to OECD 414	≥ 20000 ppm	20 days (7h / day)	Rat (male)	No effect	Stomach	Experimental value
Maternal toxicity (Inhalation (vapours))	NOAEL	Equivalent to OECD 414	16000 ppm	20 days (7h / day)	Rat (female)	No effect		Experimental value
Effects on fertility (Oral (drinking water))	NOAEL (P)	Equivalent to OECD 416	20700 mg/kg bw/day	18 week(s)	Mouse (male / female)	No effect		Experimental value

### Conclusion

Not classified for reprotoxic or developmental toxicity

### Toxicity other effects

#### AlcoSol

#### butanone

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
			Skin	Skin dryness or cracking			Literature study Skin

### Chronic effects from short and long-term exposure

#### AlcoSol

No effects known.

### 11.2. Information on other hazards

No evidence of endocrine disrupting properties

## SECTION 12: Ecological information

### 12.1. Toxicity

#### AlcoSol

No (test) data on the mixture available

Judgement is based on the relevant ingredients

# AlcoSol

## butanone

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	2993 mg/l	96 h	Pimephales promelas	Static system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	EC50	OECD 202	308 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	1972 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish								Data waiving
Long-term toxicity aquatic crustacea								Data waiving
Toxicity aquatic micro-organisms	Toxicity threshold	Equivalent to DIN 38412/8	1150 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value

## ethanol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	US EPA	15300 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value
Acute toxicity crustacea	LC50	ASTM E729-80	5012 mg/l	48 h	Ceriodaphnia dubia	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	ErC50	Equivalent to OECD 201	275 mg/l	3 day(s)	Chlorella vulgaris	Static system	Fresh water	Experimental value; Nominal concentration
Long-term toxicity fish	ChV	US EPA	245 mg/l	30 day(s)	Pisces		Fresh water	QSAR; Lethal
Long-term toxicity aquatic crustacea	NOEC		9.6 mg/l	9 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Nominal concentration
Toxicity aquatic micro-organisms	EC50		5800 mg/l	4 h	Paramecium caudatum	Static system	Fresh water	Experimental value; Nominal concentration

## Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

## 12.2. Persistence and degradability

### butanone

#### Biodegradation water

Method	Value	Duration	Value determination
OECD 301D	98 %; Oxygen consumption	28 day(s)	Experimental value

#### Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	96.295 h	1.5E6 /cm <sup>3</sup>	Calculated value

### ethanol

#### Biodegradation water

Method	Value	Duration	Value determination
	84 %; Oxygen consumption	20 day(s)	Experimental value

#### Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
	40 h	500000 /cm <sup>3</sup>	Calculated value

## Conclusion

### Water

Contains non readily biodegradable component(s)

## 12.3. Bioaccumulative potential

### AlcoSol

#### Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

### butanone

#### Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		0.3	40 °C	Experimental value

# AlcoSol

## ethanol

### BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		1 - 4.5	72 h	Cyprinus carpio	Read-across

### Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 107		-0.35	24 °C	Experimental value

### Conclusion

Does not contain bioaccumulative component(s)

## 12.4. Mobility in soil

### butanone

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.654 - 1.281	Calculated value

### ethanol

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc		0	Calculated value

#### Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	53.2 %		0.1 %	13.7 %	33.1 %	QSAR

### Conclusion

Contains component(s) with potential for mobility in the soil

Contains component(s) that adsorb(s) into the soil

## 12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

## 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

## 12.7. Other adverse effects

### AlcoSol

#### Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

#### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

### butanone

#### Groundwater

Groundwater pollutant

### ethanol

#### Groundwater

Groundwater pollutant

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

##### European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

07 06 04\* (wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics: other organic solvents, washing liquids and mother liquors). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste.

Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

#### 13.1.3 Packaging/Container

##### European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

# AlcoSol

## SECTION 14: Transport information

### Road (ADR)

14.1. UN number	UN number	1170
14.2. UN proper shipping name	Proper shipping name	ethanol solution (ethyl alcohol solution)
14.3. Transport hazard class(es)	Hazard identification number	33
	Class	3
	Classification code	F1
14.4. Packing group	Packing group	II
	Labels	3
14.5. Environmental hazards	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	144
	Special provisions	601
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

### Rail (RID)

14.1. UN number	UN number	1170
14.2. UN proper shipping name	Proper shipping name	ethanol solution (ethyl alcohol solution)
14.3. Transport hazard class(es)	Hazard identification number	33
	Class	3
	Classification code	F1
14.4. Packing group	Packing group	II
	Labels	3
14.5. Environmental hazards	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	144
	Special provisions	601
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

### Inland waterways (ADN)

14.1. UN number	UN number	1170
14.2. UN proper shipping name	Proper shipping name	ethanol solution (ethyl alcohol solution)
14.3. Transport hazard class(es)	Class	3
	Classification code	F1
14.4. Packing group	Packing group	II
	Labels	3
14.5. Environmental hazards	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	144
	Special provisions	601
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

### Sea (IMDG/IMSBC)

14.1. UN number	UN number	1170
14.2. UN proper shipping name	Proper shipping name	ethanol solution (ethyl alcohol solution)
14.3. Transport hazard class(es)	Class	3
14.4. Packing group	Packing group	II

# AlcoSol

Labels	3
<b>14.5. Environmental hazards</b>	
Marine pollutant	-
Environmentally hazardous substance mark	no
<b>14.6. Special precautions for user</b>	
Special provisions	144
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
<b>14.7. Maritime transport in bulk according to IMO instruments</b>	
Annex II of MARPOL 73/78	Not applicable, based on available data

## Air (ICAO-TI/IATA-DGR)

<b>14.1. UN number</b>	
UN number	1170
<b>14.2. UN proper shipping name</b>	
Proper shipping name	ethyl alcohol solution
<b>14.3. Transport hazard class(es)</b>	
Class	3
<b>14.4. Packing group</b>	
Packing group	II
Labels	3
<b>14.5. Environmental hazards</b>	
Environmentally hazardous substance mark	no
<b>14.6. Special precautions for user</b>	
Special provisions	A180
Special provisions	A3
Special provisions	A58
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	1 L

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
35.7 % - 77 %	

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· butanone · ethanol	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
· butanone · ethanol	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopee" cushions,

Reason for revision: 1.4

Publication date: 2008-12-04

Date of revision: 2021-07-15

Revision number: 0101

BIG number: 61280

13 / 15

# AlcoSol

	pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	<ul style="list-style-type: none"> <li>– silly string aerosols,</li> <li>– imitation excrement,</li> <li>– horns for parties,</li> <li>– decorative flakes and foams,</li> <li>– artificial cobwebs,</li> <li>– stink bombs.</li> </ul> <p>2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: "For professional users only".</p> <p>3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.</p> <p>4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.</p>
· butanone	<p>Substances falling within one or more of the following points:</p> <p>(a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008:</p> <ul style="list-style-type: none"> <li>– carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following exposure by inhalation</li> <li>– reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation</li> <li>– skin sensitiser category 1, 1A or 1B</li> <li>– skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2</li> <li>– serious eye damage category 1 or eye irritant category 2</li> </ul> <p>(b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European Parliament and of the Council</p> <p>(c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex (d) substances listed in Appendix 13 to this Annex.</p> <p>The ancillary requirements in paragraphs 7 and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of this entry.</p>	Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081

## National legislation Belgium

### AlcoSol

Numéro d'autorisation Belgique (des produits biocides)	BE-REG-00172
--	--------------

## National legislation The Netherlands

### AlcoSol

Waterbezwaarlijkheid	B (4); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

### butanone

Huidopname (wettelijk)	2-Butanon; H
------------------------	--------------

### ethanol

Huidopname (wettelijk)	Ethanol; H
------------------------	------------

SZW - Lijst van kankerverwekkende stoffen	Ethanol; Listed in SZW-list of carcinogenic substances
---	--

SZW - Lijst van voor de voortplanting giftige stoffen (ontwikkeling)	ethanol / ethylalcohol; Opgenomen in SZW-lijst van voor de voortplanting giftige stoffen (ontwikkeling); 1A
--	---

SZW - Lijst van voor de voortplanting giftige stoffen (vruchtbaarheid)	ethanol / ethylalcohol; Opgenomen in SZW-lijst van voor de voortplanting giftige stoffen (vruchtbaarheid); 1A
--	---

SZW - Lijst van voor de voortplanting giftige stoffen (borstvoeding)	ethanol / ethylalcohol; Opgenomen in SZW-lijst van voor de voortplanting giftige stoffen (borstvoeding)
--	---

## National legislation France

### AlcoSol

No data available

### butanone

Risque de pénétration percutanée	Méthyléthylcétone; Risque de pénétration percutanée
----------------------------------	---

Reason for revision: 1.4

Publication date: 2008-12-04

Date of revision: 2021-07-15

Revision number: 0101

BIG number: 61280

14 / 15

# AlcoSol

## National legislation Germany

### AlcoSol

WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
-----	--

### butanone

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	Butanon; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
Hautresorptive Stoffe	Butanon; H; Hautresorptiv

### ethanol

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	Ethanol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

## National legislation United Kingdom

### AlcoSol

No data available

### butanone

Skin absorption	Butan-2-one (methyl ethyl ketone); Sk
-----------------	---------------------------------------

## Other relevant data

### AlcoSol

No data available

### ethanol

TLV - Carcinogen	Ethanol; A3
IARC - classification	1; Alcohol beverages

## 15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

## SECTION 16: Other information

### Full text of any H- and EUH-statements referred to under section 3:

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
EUH066 Repeated exposure may cause skin dryness or cracking.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 1.4

Publication date: 2008-12-04

Date of revision: 2021-07-15

Revision number: 0101

BIG number: 61280

15 / 15