

Manufacturer:

OGNIOCHRON S.A.

ul. Przemysłowa 42, 34-120 Andrychów, Poland  
tel.: +48 33 875 10 70 ext. 161, e-mail: export@ogniochron.eu

www.ogniochron.eu

# ogniochron

## Application

Perfectly extinguishing without leaving any traces after usage of extinguishing agent. Recommended for protection of public spaces, such as offices, archives, schools, medical clinics, lawyer offices.



## Basic features

- Absolutely environmental friendly.
- Easy and ergonomic operation.
- Fast and effective in extinguishing.
- Economical maintenance and service.
- Cut-off valve behind the pressure indicator makes control of fire extinguisher easier.
- Construction of the valve enables temporary interruption of extinguishing.
- Possibility of multiple refilling.
- Cylinder of fire extinguisher covered with polyester paint, resistant to UV radiation.


## Quality and safety

Manufactured according to requirements of domestic and EU markets on the basis of certified quality system ISO 9001. Fulfills requirements of European Standard EN3 and Safety Directive PED 2014/68/UE.



## Technical data

Extinguishing efficiency	21A
Weight of extinguishing agent	9 l
Working agent	N <sub>2</sub>
Operation time	min. 9 s
Cylinder test pressure	27 bar
Operation pressure	15 bar
Operating temperature	+5 °C/+60 °C
Total weight	~14 kg
Fire under voltage	1000 V
Total height (A)	576 mm
Cylinder diameter (B)	185 mm



## Water extinguisher

# GW-9x A/MP

**FLUORINE FREE**



**ogniochron**  
**FIRE EXTINGUISHER**  
9 LTR DEMINERALISED WATER  
21 A

**1** PULL OUT PIN.  
**2** AIM HOSE AT BASE OF FIRE AND PRESS LEVER. USE IN UPRIGHT POSITION.

**CAN BE USED FOR EXTINGUISHING OF ELECTRIC DEVICES UP TO 1000 V - KEEP THE DISTANCE MIN. 1m**

INSPECTION SHOULD BE MADE EVERY 12 MONTHS AT LEAST. USE ONLY SPARE PARTS IN ACCORDANCE WITH APPROVED SAMPLE OF FIRE EXTINGUISHER. WARNING! THE EXTINGUISHING AGENT CAN FREEZE. REFILL FIRE EXTINGUISHER AFTER EACH USAGE!

EXTINGUISHING AGENT: 9 LITERS OF DEMINERALISED WATER  
PROPELLANT: NITROGEN 15 bar AT TEMP. +20°C  
SCOPE OF APPLICATION TEMPERATURES: +5°C TO +60°C

CERTIFICAT MPA SP 195/15 ACC. DIN-EN 3-7  
TYP GW-9x A/MP

Manufacturer: **OGNIOCHRON S.A.**  
ul. Przemysłowa 42, 34-120 Andrychów, POLAND  
tel.: +48 33 875 10 70  
e-mail: export@ogniochron.eu, www.ogniochron.eu

CE 0062

Year of production: 2025 2026 2027 2028 2029 2030